

KEY FEATURES

- 1000W RMS power capacity (AES)
- Full range cabinet
- High quality custom premium European drivers
- Proprietary 75°x50° constant directivity horn
- Birch plywood cabinet
- Touring grade coating with textured black mat finish, Scratch Resistant coating
- Tropicalized moisture free construction (hardware and drivers)

APPLICATIONS

The QX215 Loudspeaker is a 15" Two-way Loudspeaker system suitable for

- Main PA Sound Reinforcement for Live Outdoor applications with or without Subwoofers
- As Main PA for Auditoriums, Clubs & Lounge Bars
- Indoor/Outdoor DJ and Live Club Applications
- AV presentations for rental companies

SPECIFICATIONS

| | |
|------------------------------------|---|
| System Power Handling | 1000W RMS (AES) 2000W Program / 4000W Peak |
| Nominal impedance | 4 ohms |
| Frequency response -6dB half space | 45Hz - 19KHz |
| Average Sensitivity | 100dB/W/m |
| Calculated Maximum SPL / 1m | 130dB continuous 133dB Program 136dB Peak |
| Nominal Directivity | 75°x50° |
| Recommended low cut filter | 30Hz 24dB/oct in full range mode 75-100Hz with subwoofer |
| Recommended amplifier | Up to 2000W (no clip) in specified frequency response |
| LF | Celto Acoustique 2x15" (2.5" VC) |
| HF | Celto Acoustique 1" Exit (2" VC) |
| Crossover | 1.7 KHz Passive |
| Flying hardware | No |
| Connectors | NEUTRIK Speakon NL4 |
| Floor Monitor use | No |
| Pole mount | 35mm top hat |
| Cabinet | CNC made with tongue & groove assembly 15 and 18mm Russian birch plywood |
| Finish | Touring grade coating with textured black mat finish, Scratch Resistant coating |
| Size (WxHxD) | 445x1126x473mm 17.5"x44.3"x18.6" |
| Net weight | 48kg (105.8lbs) |

DRAWING

QX 215

WIRING