



KEY FEATURES

- Large format, High output dual 18" Subwoofer
- 4" long excursion voice coil
- 2000W RMS power handling
- 132dB continuous SPL and 138dB peak SPL
- High Output
- Premium European 18" LF driver with high excursion capacity for extended low frequency output
- High strength fiber-reinforced cone
- Advanced thermal management via internal heatsink on die caste chassis of driver
- Touring grade Baltic Birch plywood CNC cabinet
- Touring grade coating with textured black mat finish (Made in Europe)
- Can be used horizontally as well as vertically
- Provision for pole mounting top

APPLICATIONS

The VX 218s is a Dual 18" Touring Grade Subwoofer for bass reinforcement suitable for

- Medium to large scale PA systems
- Touring systems
- Permanent installation in large Club, Theater, Auditorium and other indoor venues
- DJ and mobile applications
- Side fills on stage

SPECIFICATIONS

System Power Handling	2000W RMS 4000W Program / 8000W Peak
Nominal impedance	4 ohms
Frequency response -6dB half space	34Hz - 250Hz
Average Sensitivity	99dB/W/m
Calculated Maximum SPL / 1m	132dB continuous 135dB Program 138dB Peak
Recommended low cut filter	35Hz 24dB/oct
Recommended amplifier	Up to 4000W (no clip)
LF	Custom Premium 2x18" (4" VC long excursion)
Connectors	NEUTRIK Speakon NL4
Pole mount	35mm top hat
Cabinet	CNC made with tongue & groove assembly 15 and 18mm Baltic birch plywood exterior grade
Finish	Touring grade coating with textured black mat finish, Scratch Resistant coating (Made in Europe)
Size (WxHxD)	1150x590x692mm 45.3"x23.2"x27.2"
Net weight	86kg (189.6lbs)

